



NuReDrain Webinar III:

Filter technologies for N removal from agricultural waters


Practical issues

- Please mute yourself.
- Feel free to ask questions in the chat.
- The webinar will be recorded.
- Handouts will be put available afterwards.

- Nutrient Removal and Recovery from Drainage water
- 1/3/2017 – 30/9/2021
- Interreg North Sea Region
- Project cost: € 2 674 405 - Fund: € 1 337 203
- 11 partners in 3 countries



Project goal




PROJECT GOALS




FILTER SYSTEMS ABLE
TO REMOVE 50% OF
N (= NITROGEN)



FILTER SYSTEMS ABLE
TO REMOVE 70% OF
P (= PHOSPHORUS)



20% MATERIAL
REUSE AS P-FERTILIZER



40 ORGANIZATIONS
ADOPTING FILTER
SYSTEMS

Agricultural waters

drainage water



greenhouse effluent




surface water




NuReDrain

water reservoir for drinking
water production



6 field cases



Greenhouse effluent
N + P removal

Drainage water
P removal

Water reservoir
P removal

Drainage water
N + P removal

Surface water
N removal

Drainage water
P removal



Zero Valent Iron for N and P removal

Adrian Florea; Hans Christian Bruun
Hansen


Environmental Chemistry

Department of Plant and Environmental
Sciences

University of Copenhagen




The Nitrogen wheel



Zero valent iron filter

- Objectives: to develop a filtration system that can remove nitrate (NO_3^-) and recover nitrogen as ammonium (NH_4^+) from agricultural drainage water.

- Field scale setup and principle



- Filter construct of three units:
 - Section 1:** ZVI unit + sand; 45 kg ZVI
 - Section 2:** Oxidation (air bubbling)
 - Section 3:** Ammonium capture (zeolite); pre-treated with NaCl; 70 kg zeolite
- Agricultural drainage water flow: 1 L/min
- Retention time: 35-45 min for each unit




ZVI



Zeolite

Nitrate removal




NO_3^- measured at
end of column 1



- High NO_3^- removal efficiency regardless the initial nitrate concentration (3 to 8 mg/L nitrate)
- Average NO_3^- reduction for the entire running period: 94%

Nitrate is converted to ammonium




NO_3^- and NH_4^+
measured at end of
column 1



- NO_3^- is converted to NH_4^+ . 100 % at start and then at about 70 % at end of the period
- Similar results as in laboratory experiment
- Incomplete conversion could be due to production of unmonitored nitrogen gas species (NO_2 , N_2O , N_2H_4)

Ammonium capture




NH_4^+ measured at
inlet and outlet of
column 3



- Almost 100 % NH_4^+ retained in zeolite over the entire running period
- No decrease of NH_4^+ retention as in laboratory experiments
- Higher efficiency of zeolite layer, as in laboratory experiments

Removal of iron(II)




Fe(II) measured at
inlet and outlet of
column 2





- 100 % of iron(II) removed through oxidation in the aeration section
- Iron(II) oxidized and iron(III)oxide ("rust") precipitated (yellow-brownish)

Phosphate is 100 % retained



- No phosphate was detected in the outlet from column 1 and 2
- Inlet phosphate concentration: 0.5 mg/L
- Phosphate sorbed to the "rust" formed and thus is fully retained

Green rust formation in ZVI unit



- Green rust (GR) is an unstable corrosion product typically produced in a low-oxygen environment and contain iron(II) and iron(III), the hydroxide (HO^-), and another anion such as carbonate(CO_3^{2-}), chloride(Cl^-) or sulphate (SO_4^{2-}).
- GR have good potential in applications such as water-purification processes and can reduce nitrate to ammonium.
- In ZVI field filter system - GR with carbonate as the interlayer anions

Investment and operationnal costs

Investment cost

	Price	Amount needed/ha/year (2000 m ³ drainage water)	Price/ha/year	Removal and recovery/ha/ year
ZVI	0,85 – 1 €/Kg	72 Kg	60 – 72 €	100% Nitrate removal
Zeolite	2,5 – 3 €/Kg	500 Kg	1250 – 1500 €	70% Ammonium formation + retention
Filter system + tubing + pumps	2000 €		2000 €	14 Kg N retained
Total:			3500 €	

Operational cost: electricity

Pros

- Nitrate can be completely removed, even at low concentrations and low temp. ✓
- Ammonium can be recovered enabling nitrogen to be recycled ✓
- Phosphate is fully removed ✓
- Iron(II) formed during ZVI corrosion can be oxidized and removed ✓
- The unit is advantageous for concentrated effluents such as from greenhouses ✓

Cons

- Nitrate removal can decrease due to passivating ZVI corrosion layers ✗
- Oxygen in drainage water will also consume ZVI ✗
- Reduction of water generates H_2 (gas in column) ✗
- Maintenance: requires aeration (pump) ✗
- High iron consumption ✗

Improvements

- Smaller ZVI particles to increase reaction efficiency
- Remove ZVI corrosion layers
- Recycling of phosphate



Q & A

Interreg

North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

Mobile constructed wetland at the Lethe river in Germany

Presented by Sascha Kochendörfer



Table of Content



OOWV

Interreg
North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

- Problem Description
- Filter Description
- Preliminary Results
- Future Work



00WV

Interreg
North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

Problem Description

Study Area



OOWV

Interreg

North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

- North-Western Germany
- River length: 36.5 km
- Catchment area: 180 km²
- Sum fish pond area: 120 ha
- Area nature reserve: 465 ha
- Status of nature reserve is threatened
 - red listed shore-weeds less competitive at high Nitrate concentrations

**(External load: 38.5 t
NO₃-N/a)**




Fig. 1: Satellite image of fish ponds (a) and Lethe spring area (b)

Measurement Sites



OOWV

Interreg

North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION




Fig. 2: Position measurement sites NU-L-1 – NU-L-8

Monitoring-Results: Lethe and Lethe-ditch



OOWV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION

- Both water courses show similar changes in nitrate concentrations
- Elevated values in winter
- Greatest relative increase of nitrate concentrations from summer to winter in the ditch (NU-L-2)
- Highest concentrations in the spring area (NU-L-7)




Fig. 3: $\text{NO}_3\text{-N}$ concentrations in Lethe river (NU-L-1, NU-L-7) and in Lethe-ditch (NU-L-2)

First Construction Site



OOWV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION




Fig. 4: First construction site

- First site was chosen, to test backwater caused by the wetlands and its suitability for ditches
- If backwater would be small we would have been permitted to move the wetland upstream, where concentrations are higher and discharge much lower

Wetland location

Obstacles for field trial



OWV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION



Fig. 5: Issues with the soil substrate during construction

- First site wasn't suitable due to high flows, high groundwater table and fine-sandy substrate
- Permits for building in natural protection area necessary but very difficult to obtain
-> suitable sites had to be dismissed



00WV

Interreg
North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

Filter Description

Second Construction Site



OOWV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION

- The plant was built on a field, above ground, that is owned by the OOWV
- Water is pumped from the Lethe river
- To solemnly test denitrification efficiency




Fig. 6: Second construction site

Wetland location



OOWV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION

Filter Description

- Transportable wetland
- Combination of:
 - Plants for aeration and nutrient uptake
 - Plastic carriers and burnt clay for microbial growth
- Plant bearing pots divided into two parts:
 - Upper part: Burnt clay, flowers
 - Lower part: Root system, carriers
- Six denitrification pots are installed
- A 50W pond pump is installed in the Lethe river for water supply (around 70 ml/s)



Fig. 7: Images of the mobile wetland

Filter Description



OOWV

Interreg
North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

- Each pot holds around 750l
 - The plastic carriers are filled with clay pebbles
 - The system holds around 1.5m³ of water
- Green nets help to avoid material to move inside the pots
- Inflow is diverted to the bottom of the pots to avoid bypass of the plastic carriers
- Costs for 6 pots around 6000 €



Fig. 8: Plastic carriers and burnt clay inside one wetland pot

Monitoring Equipment



DOVV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION

- Monitoring equipment in the inlet and outlet pipes
- TriOS – Opus multi-parameter sensors are used
- Nitrate concentrations, TSS, water temperature, CODeq and O₂ concentrations are monitored continuously



Fig. 9: Multiparameter sensor in the inflow pipe

Power Supply



00WV

Interreg
North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

- Power supply via solar modules and an electric cell as a buffer to fill the battery during the night and cloudy weather
- This setup is necessary in remote areas without access to the power grid
- High fuel consumption during cloudy weather and during night



Fig. 10: Solar panel and electric cell for power supply

Preliminary Results



OOWV

Interreg

North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

- Because of earlier pumping tests and heavy rainfalls, the pots were already filled. This explains the rising values in the output after regular pumping started
- Due to low values of Nitrate in the water before the loading phase, the biofilm might need time to grow
- During the ongoing growth phase, around 6-9% (7.4 mg/l input, 7.0 mg/l output) of input Nitrate is taken up
- Nutrient uptake is, however, expected to diminish during winter




Fig. 11: Preliminary results of Nitrate-N concentrations in inflow and outflow



00WV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION

Future Work

Future Work



OOWV

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION

- During the next weeks the power supply will be adapted to the weather conditions
 - Both solar modules will be used for the pump
 - A second electric cell will power the monitoring equipment
- Depending on the development of the denitrification efficiency of the wetland, a decrease of the water volume flow needs to be considered



OOWV

Interreg
North Sea Region

NuReDrain

European Regional Development Fund



EUROPEAN UNION

Thank you
for your attention!

Q & A


Moving Bed BioReactor treating greenhouse effluent and drainage water in Belgium

Prof. Raf Dewil
Nico Lambert
Pieter Van Aken




Nutrient filter: Moving Bed Bioreactor

- Biological denitrification in anoxic conditions



- Moving-bed Bioreactor technology
 - Biofilm growth on AnoxKaldnes® plastic carriers (K5)
 - Benefits: Limited growth of biomass, high active biomass concentration & no sludge settling problems
 - Treating high nitrate concentrations is possible



Considerations design MBBR concept

Tile-drained agricultural fields

- 50 – 200 mg NO₃/L
- High flow rates (7.5 – 15 m³/d)
- November – April

Greenhouse effluent

- 100 – 400 mg NO₃/L
- Low flow rates (3 m³/d)
- During the whole year

Design considerations

- Simple and robust system
- Low water temperatures (between 5 – 15 °C)
- Variable flow rates and nitrate concentrations
- Remote locations
- Low budget solution


Feasibility study at pilot scale

Long term experiment: 320 days




- Volume: 13 L
- Continuously stirred
- Carrier fill: 30%
- $C_0 = 150 \text{ mg NO}_3/\text{L}$
- $C/N = 8 - 10$
- Carbon source: Carbo ST
(*glycerol-based*)
- P source: H_3PO_4
- $\text{pH} = 6 - 7.5$
- Temperature controlled


Feasibility study at pilot scale



MBBR concept to treat agricultural waters




MBBR concept to treat agricultural waters



Self-assembly concept: Greenhouse effluent

- Greenhouse effluent
- Concept based on an universal cubic container: Volume = 1 m³
- Flow rate: 3 m³/day
- Investment cost: 3 000 €
- Operational cost: 1 000 €/year
- Efficiency cost: 107 €/kg NO₃-N removed



Container concept

- Drainage water from tile-drained fields
- 10 ft-container: Volume MBBR = 8 m³
- Flow rate: 15 m³/day
- Investment cost: 37 000 € (excl. solar panels)
- Operational cost: 2 660 €/year
- Average removal efficiency: 77% ($C_0 = 142 \text{ mg NO}_3/\text{L}$)
- Efficiency cost: 135 €/kg NO₃-N removed




Underground concept

- Drainage water from tile-drained fields
- Concrete well: Volume MBBR = 15 m³
- Flow rate: 15 m³/day
- Investment cost: 30 000 €
- Operational cost: 2 830 €/year
- Efficiency cost: 105 €/kg NO₃-N removed



Underground concept



Q & A

Acknowledgements

Interreg
North Sea Region
NuReDrain
European Regional Development Fund



EUROPEAN UNION



Interreg
North Sea Region

European Regional Development Fund



EUROPEAN UNION



**Provincie
Antwerpen**



**Provincie
Oost-Vlaanderen**
Voor ieder van ons



west-vlaanderen
de gedreven provincie